

## CCM\_L

Compact microphone  
(pg. 48 ff., 76 ff.)

adjustable-height stand  
**STV 900/1400 L3Ug**, (pg. 58)

straight extension tube, e.g. **RL 700g**  
(pg. 59)

straight extension tube for mounting in table surface  
**RLG 350 Ug**  
(pg. 62)

gooseneck for mounting in table surface  
**S 250 L5Ug**  
(pg. 62)

desk stand  
**TR 200 Lg**  
(pg. 65)

desk stand  
**TSR 200 Lg**,  
(pg. 65)

Stereo  
see page 83 ff.

Y-cable **KLY I** (pg. 113)

adapter cable to XLR-5M:  
**KS 5IU** (pg. 113)

Y-cable **KLY SU** (pg. 113)

**AK SUI2U**  
adapter cable  
XLR-5F  
to 2 x XLR-3M  
(pg. 112)

adapter cable  
**K 5 LU**  
(Lemo /XLR-3M,  
included with  
CCM\_L)  
(pg. 113)

low-cut filter  
**LC 60 U**  
or  
**LC 120 U**  
(pg. 110)

inline attenuator  
**MDZ**  
(pg. 111)



**VMS 5 U**, microphone preamplifier with MIS matrix  
(pg. 106)

## CCM\_U

Compact microphone with permanently attached cable; (special version, pg. 48 and 76 ff.)



**T2 CCM 4**  
movable twin table microphone, pg. 66



**C2 CCM 4**  
twin table microphone, pg. 64

all signals shown above are balanced